

QuickE

Electric Screwdriver SLOKY



Kit Contents:

0-TPK-ETS-16K-3.0

Handle							
QuickE							
Adapters							
	Nm	0.6	0.9	1.2	1.4	2.0	3.0
	In-lb	5.3	8.0	10.6	12.4	17.7	26.6
Bits							
	50mm	TX6	TX7	TX8	TX9	TX10	TX15
		6IP	7IP	8IP	9IP	10IP	15IP
		H1.5		H2.0		H2.5	H3.0

0-TPK-ETS-16K-5.0

Handle							
QuickE							
Adapters							
	Nm	0.9	1.2	1.4	2.0	3.0	5.0
	In-lb	8.0	10.6	12.4	17.7	26.6	44.3
Bits							
	50mm	TX7	TX8	TX9	TX10	TX15	TX20
		7IP	8IP	9IP	10IP	15IP	20IP
			H2.0		H2.5	H3.0	H4.0



QuickE Specification:

- For both manual and electric modes.
- Electric screw fastening with a protection function to prevent damage.
- 1/4" Hex drive.
- Built-in battery overcharging protection.
- LED light & Micro USB charging port.
- Rotation mode : Clockwise & Counterclockwise.

SLOKY

No Load Rotation Speed (max.)

300 r.p.m.

Ambient Temperature for charging

0-40°C

Max. Torque in Electric Mode

0.5 Nm

Max. Torque in Manual Mode

8.0 Nm

Length x Width x Height

150 x 40 x 40 mm

Drive Size

1/4" Hex (6.35 mm)

Charging Method

Micro USB 5V 1A

Battery Capacity

1.5 Ah

Battery Type

Lithium-ion

Battery Voltage

3.6V

Weight

186 g

Scan for user manual



Why Torque Control is important?

Increased tool life of fasteners. Deliver right tightening force to precise parts, no more over tightening. Enhance the function of both tightened parts and connected parts. Allows any user to deliver precision torque control, SOP is built. Apply for various applications.